931446A

Angled industrial flush socket 3P+E, 63A 400V~. IP67.



Industrial flush-mount base with angled design, featuring 3 poles + earth, rated at 63A 400V~. The IP67 rating ensures protection in harsh environments with water and dust exposure. The inclined shape enables ergonomic plug connections. Ideal for heavy-duty industrial installations.

Features

Common applications	Industrial environments (factories, warehouses, etc.)
Type	Fitted socket outlet
No. of poles	3P + T
Type of terminal connection	Screw connection
Earth position	6h
Frame for Indubox	MR1363
Nominal current	63A
Nominal voltage	400V
Color	Red

Technical data

Protection Degree (IK)	IK09
Impact shock resistance	Strong
Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	125 °C
Ambient operating temperature	-5 °C ; +40 °C
Dimensional stability	-25 °C -> +80 °C
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60309-1:2023 UNE-EN 60309-2:2023
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220042971
EAN code container	8423220042971
EAN code packaging	18423220042978
Units packaging	1
Units carton	2
Pallet Units	99999
Packaging Measures cm	29x18,5x14
Unit weight (g)	553,6
Container Weight (Kg)	0,5536
Packaging Weight (Kg)	1,2422
Tariff code	85366990

Documentation and downloads

Safety Information (0.38MB)

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com