939442

Industrial surface interlocked socket 3P+E, 16A 400V~. IP67



Wall-mounted industrial base with interlock system, fitted with 3 poles + earth, rated at 16A and 400V~. The interlock prevents disconnection under load, ensuring safe operation. With IP67 protection, it offers full sealing against dust and water, suitable for harsh environments or outdoor use. Perfect for high-power three-phase industrial applications.

Features

Common applications	Industrial environments (factories, warehouses, etc.)
Type	Surface Flush sockets
No. of poles	3P + T
Type of terminal connection	Screw connection
Earth position	6h
Interlocking	Yes
Nominal current	16A
Nominal voltage	400V
Color	Red

Technical data

Protection Degree (IK)	IK09
Impact shock resistance	Strong
Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	125 °C
Ambient operating temperature	-5 °C ; +40 °C
Dimensional stability	-25 °C -> +80 °C
Free of halogens	Yes

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60309-1:2023 UNE-EN 60309-2:2023
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220227682
EAN code container	8423220227682
EAN code packaging	18423220227689
Units packaging	1
Units carton	10
Pallet Units	8000
Packaging Measures cm	36x27,5x18,5
Unit weight (g)	730,68
Container Weight (Kg)	0,73068
Packaging Weight (Kg)	7,3068
Tariff code	85366990

Documentation and downloads

Safety Information (0.38MB)

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com