

## Industrial surface interlocked socket 3P+E, 16A 400V~. IP67

Wall-mounted industrial base with interlock system, fitted with 3 poles + earth, rated at 16A and 400V~. The interlock prevents disconnection under load, ensuring safe operation. With IP67 protection, it offers full sealing against dust and water, suitable for harsh environments or outdoor use. Perfect for high-power three-phase industrial applications.



### Features

Common applications	Industrial environments (factories, warehouses, etc.)
Type	Surface Flush sockets
No. of poles	3P + T
Type of terminal connection	Screw connection
Earth position	6h
Interlocking	Yes
Nominal current	16A
Nominal voltage	400V
Color	Red

### Technical data

Protection Degree (IK)	IK09
Impact shock resistance	Strong
Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	125 °C
Ambient operating temperature	-5 °C ; +40 °C
Dimensional stability	-25 °C -> +80 °C
Free of halogens	Yes

## Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60309-1:2023 UNE-EN 60309-2:2023
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

## Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

## Logistics and packaging

Unit EAN code	8423220227682
EAN code container	8423220227682
EAN code packaging	18423220227689
Units packaging	1
Units carton	10
Pallet Units	8000
Packaging Measures cm	36x27,5x18,5
Unit weight (g)	730,68
Container Weight (Kg)	0,73068
Packaging Weight (Kg)	7,3068
Tariff code	85366990

## Documentation and downloads



Safety Information (0.38MB)