

Automatic cable reel with 4 sockets 2P+E, 16A 250V~. 15 m of cable H05RR-F 3G1.5 mm². IP44

15-meter automatic cable reel with four sockets 2P+T, 16A 250V~ and H05RR-F 3G1.5 mm² cable. IP44. Max power: 3000W when fully extended, 1000W when coiled. With the possibility of being fixed to the ground.



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
No. of bases	4
Basic characteristics	Schuko 2P+E, 16A 250V~
Plug features	Schuko 2P+E, 16A 250V~
Maximum power (extended cable)	3.000 W
Maximum power (coiled cable)	1.000 W
Bases with lid	Yes
Cable length	15 m.
Cable Features	H05RR-F 3x1,5mm ²
Winding type	Automatic

Technical data

Insulation class	Class II
Fire resistance (GWEPT)	650/750 °C
Heat resistance (Ball pressure)	70/125 °C

Regulations

CE marking	Yes
------------	-----

According to Regulations UNE/EN	UNE-EN 61242:1998
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220065826
EAN code container	8423220065826
EAN code packaging	18423220065823
Units packaging	1
Units carton	2
Pallet Units	64
Packaging Measurements cm	33,5x30x0,1
Packaging Measures cm	40x32,5x36,5
Unit weight (g)	5021
Container Weight (Kg)	5,036
Packaging Weight (Kg)	10,725
Tariff code	85444290

Documentation and downloads



Safety Information (0.38MB)