

## Cable reel with 3 sockets 2P+E, 16A 250V~. + 2 USB sockets. 5 m of cable H05VV-F 3G1,5 mm<sup>2</sup>.

Cable reel for domestic or professional use, featuring 3 2P+T 16A 250V~ sockets and 2 USB ports 5V 2.4A (total 12W), ideal for powering both electrical and electronic devices. Supplied with 5 m of H05VV-F 3G1.5 mm<sup>2</sup> cable and an ergonomic plug handle. Supports up to 3200W extended and 1100W retracted. Includes thermal limiter for safety. Compact and functional design.



### Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
No. of bases	3
Basic characteristics	Schuko 2P+E, 16A 250V~
Plug features	Schuko 2P+E, 16A 250V~
Maximum power (extended cable)	3.200 W
Maximum power (coiled cable)	1.100 W
Cable length	5 m.
Cable Features	H05VV-F 3x1,5mm <sup>2</sup>
Winding type	Manual

### Technical data

Insulation class	Class II
Heat resistance (Ball pressure)	70/125 °C

### Regulations

CE marking	Yes
According to Regulations UNE/EN	UNE-EN 61242:1998

In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
--	-----

According to European Directive 2014/35 / EU. Low voltage directive	Yes
---	-----

## Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
---	-----

According to European Directive 2012/19/UE (RAEE2)	Yes
--	-----

According to Regulations (RoHS)	UNE-EN IEC 63000:2022
---------------------------------	-----------------------

## Logistics and packaging

Unit EAN code	8423220221826
---------------	---------------

EAN code container	8423220221826
--------------------	---------------

EAN code packaging	18423220221823
--------------------	----------------

Units packaging	1
-----------------	---

Units carton	4
--------------	---

Pallet Units	360
--------------	-----

Packaging Measures cm	35,5x18,5x18,5
-----------------------	----------------

Unit weight (g)	895
-----------------	-----

Container Weight (Kg)	0,895
-----------------------	-------

Packaging Weight (Kg)	4,58
-----------------------	------

Tariff code	85444290
-------------	----------

## Documentation and downloads



Commercial doc. (2.64MB)



Safety Information (0.38MB)