

Cable reel with 4 sockets 2P+E, 16A 230V~. 3 m of cable H05VV-F 3G1,5 mm².

Domestic cable reel with 4 sockets 2P+T 16A 230V~, equipped with 3 m H05VV-F 3G1.5 mm² cable. Max power: 3200W when extended, 1100W when coiled. Includes thermal safety limiter to prevent overheating. Ideal for home use, offices, or tasks requiring nearby and safe electrical access.



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
No. of bases	4
Basic characteristics	2P+E, 16A 230V~
Plug features	Schuko 2P+E, 16A 250V~
Maximum power (extended cable)	3.200 W
Maximum power (coiled cable)	1.100 W
Cable length	3 m.
Cable Features	H05VV-F 3x1,5mm ²
Winding type	Manual

Technical data

Insulation class	Class II
Fire resistance (GWEPT)	650/750 °C
Heat resistance (Ball pressure)	70/125 °C

Regulations

CE marking	Yes
According to Regulations UNE/EN	UNE-EN 61242:1998

In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
--	-----

According to European Directive 2014/35 / EU. Low voltage directive	Yes
---	-----

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
---	-----

According to European Directive 2012/19/UE (RAEE2)	Yes
--	-----

According to Regulations (RoHS)	UNE-EN IEC 63000:2022
---------------------------------	-----------------------

Logistics and packaging

Unit EAN code	8423220069916
---------------	---------------

EAN code container	8423220069916
--------------------	---------------

EAN code packaging	18423220069913
--------------------	----------------

Units packaging	1
-----------------	---

Units carton	10
--------------	----

Pallet Units	500
--------------	-----

Packaging Measurements cm	22x20x0,1
---------------------------	-----------

Packaging Measures cm	43x29,5x20
-----------------------	------------

Unit weight (g)	551
-----------------	-----

Container Weight (Kg)	0,561
-----------------------	-------

Packaging Weight (Kg)	6,17
-----------------------	------

Tariff code	85444290
-------------	----------

Documentation and downloads



Safety Information (0.38MB)