

Cable reel with 4 sockets 2P+E, 50m H05VV-F 2.5 mm² cable, thermal breaker and IP30

This cable reel is designed for safe use in domestic and commercial environments. It includes 4 sockets 2P+E rated 16A-250V~ and a 50-metre H05VV-F cable with 2.5 mm² section, providing higher load capacity and reducing overheating risks. It features a thermal breaker for overload protection, a brake to prevent accidental drum rotation, and an ergonomic rubber handle for easier transport. Ventilation holes enhance cooling. IP30 protection and RoHS compliance ensure reliability and safety.



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
No. of bases	4
Basic characteristics	2P+E, 16A 230V~
Plug features	Schuko 2P+E, 16A 250V~
Maximum power (extended cable)	3.200 W
Maximum power (coiled cable)	1.100 W
Cable length	50 m.
Cable Features	H05VV-F 3x2,5mm ²
Winding type	Manual

Technical data

Insulation class	Class II
Fire resistance (GWEPT)	650/750 °C
Heat resistance (Ball pressure)	70/125 °C

Regulations

CE marking	Yes
According to Regulations UNE/EN	UNE-EN 61242:1998
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220276536
EAN code container	8423220276536
EAN code packaging	18423220276533
Units packaging	1
Units carton	1
Pallet Units	68
Packaging Measurements cm	22x20x0,1
Packaging Measures cm	45x32x41
Unit weight (g)	8665
Container Weight (Kg)	8,675
Packaging Weight (Kg)	9,0766
Tariff code	85444290

Documentation and downloads



Safety Information (0.38MB)