7307350

Cable reel with 3 covered 2P+E IP55 sockets, 16A 230V~. 50 m H07RN-F 3G2.5 mm² cable



Professional construction cable reel with 3 covered 2P+E 16A 230V~ sockets. Includes 50 metres of H07RN-F 3G2.5 mm² cable, ideal for outdoor use thanks to its IP55 protection against dust and water splashes. Maximum load capacity of 3600 W when fully unwound and 1300 W when wound. A robust and versatile solution for industrial applications, workshops and construction sites.

CE RoHS

Features

Common applications	Works
No. of bases	3
Basic characteristics	2P+E, 16A 230V~
Plug features	Schuko 2P+E, 16A 250V~
Maximum power (extended cable)	3.500 W
Maximum power (coiled cable)	1.200 W
Bases with lid	Yes
Cable length	50 m.
Cable Features	H07RN-F 3x2,5mm²
Winding type	Manual

Technical data

Insulation class	Class II
Fire resistance (GWEPT)	650/750 °C
Heat resistance (Ball pressure)	70/125 °C

Regulations

CE marking	Yes

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

According to Regulations UNE/EN	UNE-EN 61242:1998
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes

Logistics and packaging

Unit EAN code	8423220296077
EAN code container	8423220296077
EAN code packaging	18423220296074
Units packaging	1
Units carton	1
Pallet Units	72
Packaging Measures cm	32x23x40.5
Packaging Weight (Kg)	9,597
Tariff code	85444290

Documentation and downloads

Safety Information (0.38MB)