

Flush distribution board, 12 modules.

Flush-mounted board with 12 modules. White frame and door. Flush dimensions 277 x 220 x 72 mm. Compact and discreet for standard recessed use.



Features

Installation method	Flush in work
Use	Domestic / Tertiary
Location type	Inside
No. Modules (18 mm)	12
Modules per row	12
Metallic DIN profile	Yes
Dimensions gap (mm) (Width x Height x Depth)	277x220x72
Dimensions (mm)	See sketch
Case material	Insulation
Frame and door material	Insulation
Case color	Black
Cap color	White
Door color	White
Door opening	Vertical
Battens included	No
Ticket type	Unfathomable
Fixation System (For surface)	Inside
Sealable	Not
Linkable	Vertically and horizontally
Lid closure system	Metal screw

Door closing system	A Pressure
Reversible door	Yes
Possibility of mounting strips	Yes (not included)
Possibility of putting lock	Yes (not included)
Separate covers or doors on the boxes	Yes
Possibility of mounting DIN rail	Yes (included)
Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Additional dimensions (mm)	See sketch

Technical data

Protection Degree (IK)	IK08
Insulation class	Class II
Fire resistance (GWEPT)	650 °C
Heat resistance (Ball pressure)	70 °C
Installation temperature	-5 °C -> +60 °C
Ambient operating temperature	-5 °C ; +60 °C
Work stress	400 Vac-1000 Vdc
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 62208:2012
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
---	--


According to European Directive
2012/19/UE (RAEE2)

Not applicable because it does not meet the definition of Electrical and Electronic
Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).


Logistics and packaging

Unit EAN code	8423220012110
EAN code container	8423220012110
EAN code packaging	18423220012117
Units packaging	1
Units carton	10
Pallet Units	150
Packaging Measurements cm	11x25x35,1
Packaging Measures cm	57,8x38,5x46
Unit weight (g)	730
Container Weight (Kg)	0,8556
Packaging Weight (Kg)	9,343
Tariff code	85371098








Sketch



Altura del marco = 23mm



Documentation and downloads

- | | |
|---|--|
|  Assembly instructions (2.09MB) |  Included accessories (0.14MB) |
|  Safety Information (0.38MB) |  Link options for enclosures (0.13MB) |
|  Dimensions table (0.15MB) |  Series replenishments (0.04MB) |
|  Distribution boards Arelos range (Solera) 2020 | |