515

Flush connection box. Ø 100 mm. Cover with metal claw.



Flush connection box. Ø 100 mm. Cover with metal claw.Depth 50 mm. 6 inputs for tube Ø 32 mm.

Features

Installation method	Flush in work
Use	Domestic / Tertiary
Location type	Inside
Dimensions inside (mm) (Width x Height x Depth)	Ø 100x50
Case material	Thermoplastic
Case color	Black
Cap color	White
No. of inlets and size (mm)	6xØ 32
Lid closure system	Metal claw
Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)

Technical data

Impact shock resistance	Medium
Insulation class	Class II
Fire resistance (GWEPT)	650 °C
Heat resistance (Ball pressure)	70 °C
Work stress	400 Vac
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60670-1:2022 UNE- EN 60670-22:2007
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes


Sustainability


According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
According to European Directive 2012/19/UE (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).


Logistics and packaging

Unit EAN code	8423220240513
EAN code container	8423220005150
EAN code packaging	18423220005157
Units packaging	6
Units carton	180
Pallet Units	2700
Packaging Measures cm	59,5x39,5x59,5
Unit weight (g)	78,2
Container Weight (Kg)	0,4792
Packaging Weight (Kg)	15,506
Tariff code	85371098

Sketch







Documentation and downloads

- Assembly instructions (0.17MB)
- Safety Information (0.38MB)
- Series replenishments (0.26MB)