


Flush connection box. 300 x 200 x 60 mm Cover with screws.

Flush connection box. 300 x 200 mm Cover with screws.Depth 60 mm. 20 inputs for Ø 40 tube. One partition walls.



Features

Installation method	For hollow wall.
Use	Domestic / Tertiary
Location type	Inside
Dimensions gap (mm) (Width x Height x Depth)	300x200x60
Case material	Thermoplastic
Case color	Black
Cap color	White
No. of inlets and size (mm)	20xØ 40
Lid closure system	Metal screw
Possibility of mounting DIN rail	Yes (not included)
Fixing system to the hollow partition.	Multi-perforated support for hollow wall black colour.
Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)

Technical data

Impact shock resistance	Medium
Insulation class	Class II
Fire resistance (GWEPT)	650 °C
Heat resistance (Ball pressure)	70 °C
Work stress	400 Vac
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60670-1:2022 UNE- EN 60670-22:2007
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
According to European Directive 2012/19/UE (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).

Logistics and packaging

Unit EAN code	8423220011984
EAN code container	8423220011984
Units packaging	1
Units carton	31
Packaging Measures cm	59,5x39,5x59,5
Unit weight (g)	432,2
Container Weight (Kg)	0,4372
Packaging Weight (Kg)	14,6832
Tariff code	85371098

Documentation and downloads

**Assembly instructions (0.17MB)**

**Series replenishments (0.26MB)**

**Safety Information (0.38MB)**