

Flush connection box. 300x500x60mm.

Flush connection box. 300 x 500 mm. White frame and door with heat dissipation grid. Depth 60 mm. 50 inputs for tube Ø 40 mm. Removable walls separator partitions.



Features

Installation method	Flush in work
Use	Domestic / Tertiary
Location type	Inside
Dimensions inside (mm) (Width x Height x Depth)	300x500x60
Case material	Insulation
Case color	Black
Cap color	White
Door color	White with heat dissipation grid.
No. of inlets and size (mm)	50 xØ 40
Linkable	Vertically and horizontally
Lid closure system	Ultra-fast metal screw
Door closing system	A Pressure
Possibility of putting lock	Yes (not included)
Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)

Technical data

Impact shock resistance	Medium
Insulation class	Class II

Fire resistance (GWEPT)	650 °C
Heat resistance (Ball pressure)	70 °C
Work stress	400 Vac
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60670-1:2022 UNE- EN 60670-22:2007
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/EU (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
According to European Directive 2012/19/EU (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).

Logistics and packaging

Unit EAN code	8423220261549
EAN code container	8423220261549
Units packaging	1
Units carton	5
Pallet Units	75
Packaging Measures cm	57,8x38,5x46
Unit weight (g)	1618
Container Weight (Kg)	1,618
Packaging Weight (Kg)	8,877
Tariff code	85371098

Documentation and downloads



Assembly instructions (0.17MB)



Safety Information (0.38MB)