

Flush efficient mechanism box in hollow partition. For 1 module. Fixing with metal claws.

Flush efficient mechanism box in hollow partition. For 1 module. Fixing with metal claws. Flush dimensions \varnothing 68 x 46 mm. 2 entries for \varnothing 16–20 mm conduit and 2 entries for \varnothing 20–25 mm conduit. Use \varnothing 68 mm hole saw.



Features

Installation method	For hollow wall.
Use	Domestic / Tertiary
Location type	Inside
No. Modules (18 mm)	1
Dimensions gap (mm) (Width x Height x Depth)	\varnothing 68 x 46 mm.
Case material	Insulation
Case color	Blue
Ticket type	Flexible membrane
No. of inlets and size (mm)	2 entradas para tubo \varnothing 16-20 y 2 entradas para tubo \varnothing 20-25 mm
Fixing system to the hollow partition.	Short metal claw
Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Lightening torque	0.30 - 0.40 Nm

Technical data

Fire resistance (GWEPT)	850 °C
Installation temperature	-5 °C -> +60 °C
Ambient operating temperature	-5 °C ; +60 °C
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60670-1:2022 UNE- EN 60670-22:2007
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
AENOR certificate	Yes
CB certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
According to European Directive 2012/19/UE (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).

Logistics and packaging

Unit EAN code	8423220266742
EAN code container	8423220266742
Units packaging	20
Units carton	320
Pallet Units	4800
Packaging Measures cm	59,5x39,5x59,5
Unit weight (g)	31
Container Weight (Kg)	0,629
Packaging Weight (Kg)	11,194
Tariff code	39259010

Documentation and downloads



Assembly instructions (3.56MB)



Commercial doc. (3.42MB)



Safety Information (0.38MB)



Mechanism boxes for dry wall, Blue range (Solera)



Mounting mechanism boxes for dry wall (Solera)