

Sealed distribution box. 11 modules. IP54.

Sealed distribution box. 11 modules. IP54.IK07. White colour. External dimensions 230 x 180 x 86 mm. Smooth laterals. Sealable. 1/4 turn closure screw.

Common applications: Domestic / tertiary outdoor environment (garden, swimming pool, parking, public road, etc.)



Features

| | |
|--|--|
| Enclosure type | Sealable layout |
| Installation method | Surface |
| Use | Domestic / Tertiary |
| Location type | Exterior and interior |
| No. Modules (18 mm) | 11 |
| Modules per row | 11 |
| Metallic DIN profile | Yes |
| Dimensions outside (mm) (width x height x depth) | 230x180x86 |
| Dimensions inside (mm) (Width x Height x Depth) | 220x170x80 |
| Case material | Insulation |
| Frame and door material | Insulation |
| Case color | White |
| Door color | Fumé |
| Door opening | Horizontal |
| Battens included | No |
| Ticket type | Smooth sides (machining inlets) |
| Fixation System (For surface) | Inside with plug (To ensure class II and IP) |
| Sealable | Yes |
| Lid closure system | 1/4 turn screw with spring |

| | |
|---------------------------------------|--------------------|
| Door closing system | Handle |
| Possibility of mounting strips | Yes (not included) |
| Separate covers or doors on the boxes | Yes |
| Possibility of mounting DIN rail | Yes (included) |
| Valid for photovoltaic installations | Yes |

Technical data

| | |
|----------------------------------|---------------|
| Protection Degree (IP) | IP54 |
| Protection Degree (IK) | IK07 |
| Impact shock resistance | Medium |
| Insulation class | Class II |
| Fire resistance (GWT) | 650°C |
| Heat resistance (Ball pressure) | 70°C |
| Installation temperature | -5°C -> +60°C |
| Work stress | 400 Vca |
| UV resistance | Yes |
| Free of halogens | Yes |
| Suitable for saline environments | Yes |

Regulations

| | |
|---|-------------------|
| CE marking | Yes |
| UK marking | Yes |
| CMim marking | Yes |
| According to Regulations UNE/EN | UNE-EN 62208:2012 |
| According to REBT | Yes |
| According to European Directive 2014/35 / EU. Low voltage directive | Yes |

Sustainability

| | |
|---|--|
| According to European Directive 2011/65/EU (RoHS) | The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1 |
|---|--|

According to European Directive
2012/19/UE (RAEE2)

Not applicable because it does not meet the definition of Electrical and Electronic
Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).

Logistics and packaging

| | |
|-----------------------|----------------|
| Unit EAN code | 8423220008960 |
| EAN code container | 8423220008960 |
| EAN code packaging | 18423220008967 |
| Units Container | 1 |
| Units Packaging | 28 |
| Pallet Units | 420 |
| Packaging Measures cm | 59,5x59,5x39,5 |
| Unit weight (gr) | 635 |
| Container Weight (Kg) | 0,64 |
| Packaging Weight (Kg) | 18,78 |
| Tariff code | 85371098 |

Sketch

