

Flush distribution box of 14 modules. With metallic frame and door, graphite Colour

Flush distribution box of 14 modules. With metallic frame and door Graphite colour. Grey box and white cover, thermoplastic material. Flush dimensions 333 x 300 x 88 mm. Thermal dissipation 30W.



Features

Installation method	Flush in work
Use	Domestic / Tertiary
Location type	Inside
No. Modules (18 mm)	14
Modules per row	14
Metallic DIN profile	Yes
Dimensions inside (mm) (Width x Height x Depth)	330 x 297 x 88
Dimensions gap (mm) (Width x Height x Depth)	330 x 297 x 88
Case material	Insulation
Frame and door material	Metallic stainless
Case color	Grey (RAL7035)
Cap color	White
Door color	Graphite
Door opening	Horizontal
Battens included	Yes (Screw terminals)
Strip type	Ground
No. of terminals and size	13x6 mm ² + 4x16 mm ²
Ticket type	Unfathomable
Sealable	Yes
Linkable	Vertically and horizontally

Lid closure system	1/4 turn screw without spring
Door closing system	Handle
Reversible door	Yes
Possibility of mounting strips	Yes (included)
Possibility of putting lock	Yes (not included)
Possibility of mounting plate	Yes (not included)
Possibility of mounting DIN rail	Yes (included)
Alignment marks	Both
Possibility of mounting .PL-MP28 plate	Yes (not included)
With grommets at the bottom to fix the tubes or cables with cable ties, quantity	Yes
With recessed hole marking system	Yes
Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)

Technical data

Protection Degree (IK)	IK07
Insulation class	Class II
Fire resistance (GWEPT)	650 °C
Heat resistance (Ball pressure)	70 °C
Installation temperature	-5 °C -> +60 °C
Work stress	<1000 Vac ; 1500 Vdc
Thermal power dissipated	30 W
UV resistance	Yes
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 62208:2012
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes

According to European Directive 2014/35 / Yes
EU. Low voltage directive


Sustainability

According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
According to European Directive 2012/19/UE (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).

Logistics and packaging

Unit EAN code	8423220246140
EAN code container	8423220246140
EAN code packaging	18423220246147
Units packaging	1
Units carton	6
Pallet Units	72
Packaging Measurements cm	37x34x11
Packaging Measures cm	71,5x34,5x39
Unit weight (g)	2057,8
Container Weight (Kg)	2,3278
Packaging Weight (Kg)	14,7208
Tariff code	85371098

Sketch



Documentation and downloads

-  [Included accessories \(0.13MB\)](#)
-  [Series replenishments \(0.1MB\)](#)
-  [Mounting flush distribution board \(Solera\)](#)
-  [Safety Information \(0.38MB\)](#)
-  [Flush distribution board \(Solera\) \(2020\)](#)