

Flush distribution box of 42 modules. With metallic frame and door, graphite colour.

Flush distribution box of 42 modules. With metallic frame and door, graphite colour. 3 rows. Grey box and white cover, thermoplastic material. Flush dimensions 333 x 620 x 88 mm. Thermal dissipation 35W.



Features

Installation method	Flush in work
Use	Domestic / Tertiary
Location type	Inside
No. Modules (18 mm)	42
Modules per row	14
Removable frame	Yes
Metallic DIN profile	Yes
Dimensions outside (mm) (width x height x depth)	362X643X88
Dimensions gap (mm) (Width x Height x Depth)	333x620x88
Case material	Insulation
Frame and door material	Metallic stainless
Case color	Grey (RAL7035)
Cap color	White
Door color	Graphite
Door opening	Horizontal
Battens included	Yes (Screw terminals)
Strip type	Neutral + Ground
No. of terminals and size	18x6 mm ² + 6x16 mm ² + 5x6 mm ²

Ticket type	Unfathomable
Sealable	Yes
Linkable	Vertically and horizontally
Lid closure system	1/4 turn screw without spring
Door closing system	Handle
Reversible door	Yes
Possibility of mounting strips	Yes (included)
Possibility of putting lock	Yes (not included)
Possibility of mounting plate	Yes (not included)
Possibility of mounting DIN rail	Yes (included)
Alignment marks	Both
Possibility of mounting .PL-MP28 plate	Yes (not included)
With grommets at the bottom to fix the tubes or cables with cable ties, quantity	Yes
With recessed hole marking system	Yes
Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)

Technical data

Protection Degree (IK)	IK07
Insulation class	Class II
Fire resistance (GWEPT)	650 °C
Heat resistance (Ball pressure)	70 °C
Installation temperature	-5 °C -> +60 °C
Work stress	<1000 Vac ; 1500 Vdc
Thermal power dissipated	35 W
UV resistance	Yes
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes

According to Regulations UNE/EN	UNE-EN 62208:2012
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes


Sustainability

According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
According to European Directive 2012/19/UE (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).

Logistics and packaging

Unit EAN code	8423220246164
EAN code container	8423220246164
EAN code packaging	18423220246161
Units packaging	1
Units carton	3
Pallet Units	36
Packaging Measurements cm	65x37,5x11
Packaging Measures cm	66x36,5x39
Unit weight (g)	4245
Container Weight (Kg)	4,585
Packaging Weight (Kg)	14,504
Tariff code	85371098

Sketch



Documentation and downloads

-  Included accessories (0.13MB)
-  Series replenishments (0.05MB)
-  Mounting flush distribution board (Solera)
-  Safety Information (0.38MB)
-  Flush distribution board (Solera) (2020)