

Flush distribution box of 56 modules. With metallic frame and door, graphite colour.

Flush distribution box of 56 modules. With metallic frame and door, graphite colour. 4 rows. Grey box and white cover thermoplastic material. Flush dimensions 333 x 752 x 88 mm. Thermal dissipation 40W.



Features

| | |
|--|---|
| Installation method | Flush in work |
| Use | Domestic / Tertiary |
| Location type | Inside |
| No. Modules (18 mm) | 56 |
| Modules per row | 14 |
| Removable frame | Yes |
| Metallic DIN profile | Yes |
| Dimensions outside (mm) (width x height x depth) | 362X778X88 |
| Dimensions gap (mm) (Width x Height x Depth) | 333x752x88 |
| Case material | Insulation |
| Frame and door material | Metallic stainless |
| Case color | Grey (RAL7035) |
| Cap color | White |
| Door color | Graphite |
| Door opening | Horizontal |
| Battens included | Yes (Screw terminals) |
| Strip type | Neutral + Ground |
| No. of terminals and size | 28x6 mm ² + 6x16 mm ² + 5x6 mm ² |

| | |
|--|---|
| Ticket type | Unfathomable |
| Sealable | Yes |
| Linkable | Vertically and horizontally |
| Lid closure system | 1/4 turn screw without spring |
| Door closing system | Handle |
| Reversible door | Yes |
| Possibility of mounting strips | Yes (included) |
| Possibility of putting lock | Yes (not included) |
| Possibility of mounting plate | Yes (not included) |
| Possibility of mounting DIN rail | Yes (included) |
| Alignment marks | Both |
| Possibility of mounting .PL-MP28 plate | Yes (not included) |
| With grommets at the bottom to fix the tubes or cables with cable ties, quantity | Yes |
| With recessed hole marking system | Yes |
| Common applications | Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.) |

Technical data

| | |
|---------------------------------|----------------------|
| Protection Degree (IK) | IK07 |
| Insulation class | Class II |
| Fire resistance (GWEPT) | 650 °C |
| Heat resistance (Ball pressure) | 70 °C |
| Installation temperature | -5 °C -> +60 °C |
| Work stress | <1000 Vac ; 1500 Vdc |
| Thermal power dissipated | 40 W |
| UV resistance | Yes |
| Free of halogens | Yes |

Regulations

| | |
|--------------|-----|
| CE marking | Yes |
| UK marking | Yes |
| CMim marking | Yes |

| | |
|--|-------------------|
| According to Regulations UNE/EN | UNE-EN 62208:2012 |
| In accordance with the Low Voltage Electrotechnical Regulations (REBT) | Yes |
| According to European Directive 2014/35 / EU. Low voltage directive | Yes |

Sustainability

| | |
|--|---|
| According to European Directive 2011/65/UE (RoHS) | The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1 |
| According to European Directive 2012/19/UE (RAEE2) | Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II). |

Logistics and packaging

| | |
|---------------------------|----------------|
| Unit EAN code | 8423220246171 |
| EAN code container | 8423220246171 |
| EAN code packaging | 18423220246178 |
| Units packaging | 1 |
| Units carton | 3 |
| Pallet Units | 36 |
| Packaging Measurements cm | 79x37,5x11 |
| Packaging Measures cm | 80x36,5x39 |
| Unit weight (g) | 5060 |
| Container Weight (Kg) | 5,55 |
| Packaging Weight (Kg) | 17,348 |
| Tariff code | 85371098 |

Sketch



Documentation and downloads

-  [Included accessories \(0.13MB\)](#)
-  [Series replenishments \(0.05MB\)](#)
-  [Mounting flush distribution board \(Solera\)](#)
-  [Safety Information \(0.38MB\)](#)
-  [Flush distribution board \(Solera\) \(2020\)](#)

