822

Connection sealed box without cones. Grey colour. IP65. External dimensions 362 x 362 x 140 mm. Internal dimensions 354x354x131 mm



Connection sealed box without cones. Grey colour. IP65. IK08. External dimensions 362 x 362 x 140 mm. Internal dimensions 354 x 354 x 131 mm. Smooth cover and lateral. With centricity points. Quick closure with stainless screws.

Features

Installation method	Surface
Use	Industrial
Location type	Exterior and interior
Dimensions outside (mm) (width x height x depth)	362x362x140
Dimensions (mm)	See sketch
Case material	Thermoplastic
Case color	Grey (RAL7035)
Cap color	Grey (RAL 7035)
Battens included	No
Ticket type	With centricity points.
Fixation System (For surface)	Ref.KIT1300SOP (not included). For all INDUBOX except for Ref. 1303 and 1304
Sealable	Yes
Linkable	Vertically and horizontally
Lid closure system	Ultra-fast metal screw
Possibility of mounting strips	Yes (not included)
Possibility of mounting plate	Yes (not included)
Possibility of mounting DIN rail	Yes (not included)
Captive screw	Yes
Drain type	Deflowable Drainage

Possibility of mounting .PL-MP28 plate	Yes (not included)
Captive Lid	Yes
Valid for photovoltaic installations	Yes
Common applications	Industrial environments (factories, warehouses, etc.)
Additional dimensions (mm)	See sketch

Technical data

Protection Degree (IK)	IK08
Impact shock resistance	Strong
Insulation class	Class II
Fire resistance (GWEPT)	650 ºC
Heat resistance (Ball pressure)	70 ºC
Installation temperature	-25 ºC -> +60 ºC
UV resistance	Yes
Free of halogens	Yes
Suitable for saline environments	Yes

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60670-1:2022 UNE-EN 60670-22:2007
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes


Sustainability

According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
According to European Directive 2012/19/UE (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).

Logistics and packaging

Unit EAN code	8423220227453
EAN code container	8423220227453
EAN code packaging	18423220227450
Units packaging	1
Units carton	6
Pallet Units	60
Packaging Measures cm	56x37,5x70,5
Unit weight (g)	1674
Container Weight (Kg)	1,688
Packaging Weight (Kg)	11,104
Tariff code	85381000

Sketch



Documentation and downloads

- **Assembly instructions (1.16MB)**
- **Safety Information (0.38MB)**
- **Certificate (0.48MB)**
- **Series replenishments (0.05MB)**

Industrial cabinets IP65, IK08 (Solera) (Ed. 2024)