

Mounted sealed box 220 x 170 x 80 mm with 1 Schuko socket 2P+T, 16A, 250V~ + 1 CE socket 3P+T 16A 400V~

Mounted sealed box 220 x 170 x 80 mm with 1 Schuko socket 2P+T, 16A, 250V~ + 1 CE socket 3P+T 16A 400V~

Common applications: Industrial environments (factories, warehouses, etc.)



Features

Enclosure type	Connection and derivation
Installation method	Surface
Use	Domestic / Tertiary
Location type	Exterior and interior
Dimensions outside (mm) (width x height x depth)	230x180x88
Dimensions inside (mm) (Width x Height x Depth)	220x170x80
Case material	Insulation
Case color	Grey (RAL7035)
Cap color	Grey (RAL 7035)
Ticket type	Smooth sides (machining inlets)
Fixation System (For surface)	Exterior
Sealable	Yes
Lid closure system	1/4 turn screw with spring
Possibility of mounting strips	Yes (not included)
Captive screw	Yes
Captive Lid	Yes
Valid for photovoltaic installations	Yes

Technical data

Protection Degree (IP)	IP44
Protection Degree (IK)	IK08
Impact shock resistance	Strong
Insulation class	Class II
Fire resistance (GWEPT)	650 °C
Heat resistance (Ball pressure)	70 °C
Ambient operating temperature	-5 °C ; +60 °C
Work stress	<1000 Vac ; 1500 Vdc
UV resistance	Yes
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60670-1:2022 UNE- EN 60670-22:2007
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	The box does not correspond to the definition of Electrical and Electronical Equipment (EEE), but the included devices are affected individually.
According to European Directive 2012/19/UE (RAEE2)	The box does not correspond to the definition of Electrical and Electronical Equipment (EEE), but the included devices are affected individually.

Logistics and packaging

Unit EAN code	8423220083592
EAN code container	8423220083592
EAN code packaging	18423220083599

Units packaging	1
Units carton	6
Pallet Units	210
Packaging Measures cm	59,5x20x37,5
Unit weight (g)	700
Container Weight (Kg)	0,70
Packaging Weight (Kg)	4,74
Tariff code	85381000

Documentation and downloads

 [Junction boxes IP65/55, IK07-08-09 \(Solera\)](#)

 [Mounting junction boxes \(Solera\)](#)