


Cable outlet 4 x 2.5 mm². Flush.

Cable outlet 4 x 2.5 mm². Flush.White colour. Without frame. Screw connection.



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanism type	Cable outlet
Type of installation	Flush
Nominal voltage	250V~ (50/60 Hz)
Connection type	Screw connection
Flexible cable section	Up to 2.5 mm ²
Rigid cable section	Up to 2.5 mm ²

Technical data

Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	70/125 °C
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60998-1:2005
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes

According to European Directive 2014/35 / Yes
EU. Low voltage directive

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220095328
EAN code container	8423220085060
EAN code packaging	18423220085067
Units packaging	10
Units carton	120
Pallet Units	4320
Packaging Measurements cm	25,2x14x8
Packaging Measures cm	44,5x26,8x32,2
Unit weight (g)	69,4
Container Weight (Kg)	0,8336
Packaging Weight (Kg)	10,6162
Tariff code	85366990

Documentation and downloads



[Commercial doc. \(3.28MB\)](#)



[Safety Information \(0.38MB\)](#)



[Flush switches of Eruopa range \(Solera\)](#)



[Assembly flush switches form Europa range \(Solera\)](#)