ERP84



RJ11 telephone jack.

RJ11 telephone jack.Flush. White colour. Without frame.

Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanism type	RJ11 phone jack
Type of installation	Flush
Nominal voltage	250V~ (50/60 Hz)

Technical data

Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	70/125 °C
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 50173-1:2018
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220094390
EAN code container	8423220081055
EAN code packaging	18423220081052
Units packaging	10
Units carton	120
Pallet Units	4320
Packaging Measurements cm	21x14,2x8
Packaging Measures cm	44,5x32,2x22,5
Unit weight (g)	49
Container Weight (Kg)	0,6208
Packaging Weight (Kg)	8,0046
Tariff code	85366990

Documentation and downloads

Commercial doc. (3.28MB)

Safety Information (0.38MB)

Mechanism scheme table (0.91MB)

Flush switches of Eruopa range (Solera)

Assembly flush switches form Europa range (Solera)