

Cable outlet 4 x 2.5 mm². Flush.

Cable outlet 4 x 2.5 mm². Flush. Silver colour. Without frame. Screw connection.



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanism type	Cable outlet
Type of installation	Flush
Nominal voltage	250V~ (50/60 Hz)
Connection type	Screw connection
Flexible cable section	Up to 2.5 mm ²
Rigid cable section	Up to 2.5 mm ²

Technical data

Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	70/125 °C
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60998-1:2005
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes

According to European Directive 2014/35 / Yes
EU. Low voltage directive

Sustainability

According to European Directive 2011/65/UE (RoHS) Yes

According to European Directive 2012/19/UE (RAEE2) Yes

According to Regulations (RoHS) UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code 8423220235137

EAN code container 8423220234666

EAN code packaging 18423220234663

Units packaging 10

Units carton 120

Pallet Units 4320

Packaging Measurements cm 25,2x14x8

Packaging Measures cm 44,5x26,8x32,2

Unit weight (g) 69,4

Container Weight (Kg) 0,8336

Packaging Weight (Kg) 10,6162

Tariff code 85366990

Documentation and downloads



Commercial doc. (3.28MB)



Safety Information (0.38MB)



Flush switches of Eruopa range (Solera)



Assembly flush switches form Europa range (Solera)