
ERP40A



Cable outlet 4 x 2.5 mm². Flush.

Cable outlet 4 x 2.5 mm². Flush. Silver colour. Without frame. Screw connection.

Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanism type	Cable outlet
Type of installation	Flush
Nominal voltage	250V~ (50/60 Hz)
Connection type	Screw connection
Flexible cable section	Up to 2.5 mm²
Rigid cable section	Up to 2.5 mm²

Technical data

Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	70/125 °C
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60998-1:2005
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220235137
EAN code container	8423220234666
EAN code packaging	18423220234663
Units packaging	10
Units carton	120
Pallet Units	4320
Packaging Measurements cm	25,2x14x8
Packaging Measures cm	44,5x26,8x32,2
Unit weight (g)	69,4
Container Weight (Kg)	0,8336
Packaging Weight (Kg)	10,6162
Tariff code	85366990

Documentation and downloads

Assembly instructions (0.58MB)

Commercial doc. (3.28MB)

Safety Information (0.38MB)

Mechanism scheme table (0.91MB)

Flush switches of Eruopa range (Solera)

Assembly flush switches form Europa range (Solera)