

## Card switch. Flush.

Card switch. Flush.Flush. White colour. Monobloc. Screw connection.



## Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanism type	Card switch
Type of installation	Flush
Nominal voltage	250V~ (50/60 Hz)
Connection type	Screw connection
Power	3680W
Dimensions	83 x 81
Frame color	White

## Technical data

Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	70/125 °C
Free of halogens	Yes

## Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60669-1:2018

In accordance with the Low Voltage Electrotechnical Regulations (REBT) Yes

According to European Directive 2014/35 / EU. Low voltage directive Yes

## Sustainability

According to European Directive 2011/65/UE (RoHS) Yes

According to European Directive 2012/19/UE (RAEE2) Yes

According to Regulations (RoHS) UNE-EN IEC 63000:2022

## Logistics and packaging

Unit EAN code 8423220096134

EAN code container 8423220095762

EAN code packaging 18423220095769

Units packaging 10

Units carton 120

Pallet Units 4320

Packaging Measurements cm 26x14x10

Packaging Measures cm 44x27,5x40

Unit weight (g) 95


Container Weight (Kg) 1,1004

Packaging Weight (Kg) 13,9228

Tariff code 85366990

## Documentation and downloads

 [Safety Information \(0.38MB\)](#)  [Flush switches of Eruopa range \(Solera\)](#)

 [Assembly flush switches form Europa range \(Solera\)](#)