ERP20U

Blind push button 10A 250~. Mechanical locking. Monobloc. Flush.



Blind push button 10A 250~. Mechanical locking. Monobloc. Flush.White colour. Dimensions 83 x 81 mm. Screw connection.

Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanism type	Shutter button
Type of installation	Flush
Rated current	10A
Nominal voltage	250V~ (50/60 Hz)
Connection type	Screw connection
Type of operation	Rocker key
Dimensions	83 x 81
With fixing claws	Yes
Monobloc (with frame included)	Yes
Frame color	White

Technical data

Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	70/125 °C
Free of halogens	Yes

Regulations

CE marking	Yes

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60669-1:2018
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
TÜV Rheinland certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability


According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220076587
EAN code container	8423220076945
EAN code packaging	18423220076942
Units packaging	10
Units carton	120
Pallet Units	4320
Packaging Measurements cm	26x14x10
Packaging Measures cm	44x27,5x40
Unit weight (g)	94,8
Container Weight (Kg)	1,0984
Packaging Weight (Kg)	13,8988
Tariff code	85366990

Sketch

ERP20U



Documentation and downloads

- Assembly instructions (0.58MB)
- Safety Information (0.38MB)
- Mechanism scheme table (0.91MB)
- Certificate (0.09MB)
- Flush switches of Eruopa range (Solera)
- Assembly flush switches form Europa range (Solera)