

Double USB charger. Input: 230V~. Output USB: 5V. 4200 mA (Total). Standby: < 0,1 W. Flush.

Double USB charger. Input: 230V~. Output USB: 5V. 4200 mA (Total). Standby: < 0,1 W. Flush. White colour. Dimensions 83x81 mm.. Monobloc.



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanism type	Double USB
Type of installation	Flush
Rated current	2,1Adc
Nominal voltage	250V~ (50/60 Hz) - 5Vdc
Connection type	Fast connection
Dimensions	83 x 81
With fixing claws	Yes
Monobloc (with frame included)	Yes
Frame color	White

Technical data

Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	70/125 °C
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes

CMim marking	Yes
According to Regulations UNE/EN	UNE EN 62680-1:2013
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes




Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220208995
EAN code container	8423220208971
EAN code packaging	18423220208978
Units packaging	10
Units carton	120
Pallet Units	4320
Packaging Measurements cm	26x14x10
Packaging Measures cm	44x27,5x40
Unit weight (g)	94,8
Container Weight (Kg)	1,0984
Packaging Weight (Kg)	13,8988
Tariff code	85366990

Documentation and downloads

- 
[Safety Information \(0.38MB\)](#)
- 
[Flush switches of Eruopa range \(Solera\)](#)
- 
[Assembly flush switches form Europa range \(Solera\)](#)

