ERP60FU



Socket 2P+E (French), 16A 250V~. Monobloc. Flush.

Socket 2P+E (French), 16A 250V~. Monobloc. Flush.White colour. Dimensions 83 x 81 mm. With shutter. Screw connection.

Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanism type	Fixed base
Type of installation	Flush
Rated current	16A
Nominal voltage	250V~ (50/60 Hz)
Connection type	Screw connection
Dimensions	83 x 81
With fixing claws	Yes
Monobloc (with frame included)	Yes
Frame color	White

Technical data

Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	70/125 °C
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

According to Regulations	NF C61-314
According to Regulations UNE/EN	UNE-20315-1-1:2017; UNE-20315-1-2:2017
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
In accordance with the Regulation (EU) 2023/988 of the European Parliament and of the Council on general product safey	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220081604
EAN code container	8423220081628
EAN code packaging	18423220081625
Units packaging	10
Units carton	120
Pallet Units	4320
Packaging Measurements cm	26x14x10
Packaging Measures cm	44x27,5x40
Unit weight (g)	87,2
Container Weight (Kg)	1,0224
Packaging Weight (Kg)	12,9868
Tariff code	85366990

Documentation and downloads

Assembly instructions (0.58MB)

Safety Information (0.38MB)

Mechanism scheme table (0.91MB)

Flush switches of Eruopa range (Solera)

ERP60FU

Assembly flush switches form Europa range (Solera)