3366F

Sealed double socket 2P+E (French), 16A 250V~. IP44. Surface.



Sealed double socket 2P+E (French), 16A 250V~. IP44. Surface.Tube inputs up to Ø 20 mm. External dimensions 127 x 80 x 55 mm. Screw connection.

Features

Common applications	Domestic / tertiary outdoor environment (garden, swimming pool, parking, public road, etc.)
Mechanism type	Double fixed base
Type of installation	Surface
Rated current	16A
Nominal voltage	250V~ (50/60 Hz)
Connection type	Screw connection
Tube inlet	Up to Ø 20 mm
Flexible cable section	Up to 2.5 mm²
Rigid cable section	Up to 2.5 mm²
Power	3680 W
Dimensions	127 x 80 x 55
Monobloc (with frame included)	Yes
Frame color	Grey

Technical data

Insulation class	Class II
Fire resistance (GWEPT)	650/850 °C
Heat resistance (Ball pressure)	70/125 °C
Installation temperature	-5 °C -> +60 °C
Free of halogens	Yes

Regulations

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

CE marking	Yes
According to Regulations	NF C61-314
According to Regulations UNE/EN	UNE 20315-1-1:2017 UNE 20315-1-2:2017
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
NF certificate	Yes
In accordance with the Regulation (EU) 2023/988 of the European Parliament and of the Council on general product safey	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220078529
EAN code container	8423220069367
EAN code packaging	18423220069364
Units packaging	10
Units carton	60
Pallet Units	1260
Packaging Measurements cm	28x19,5x14
Packaging Measures cm	45,5x41,5x30
Unit weight (g)	204,4
Container Weight (Kg)	2,156
Packaging Weight (Kg)	13,704
Tariff code	85366990

Documentation and downloads

3366F

Assembly instructions (0.58MB)

Commercial doc. (2.27MB)

Safety Information (0.38MB)

Mechanism scheme table (0.47MB)

Watertight switch IP54/44 (Solera)

Assembly watertight switches IP54/44 (Solera)