

## Sealed double vertical socket 2P+E (French system), 16A 250V~. IP44. Surface.Vertical.

Sealed double vertical socket 2P+E (french system), 16A 250V~. IP44. Surface. Screw connection. Tube inputs up to Ø 20 mm. External dimensions 80 x 127 x 55 mm.



### Features

Common applications	Domestic / tertiary outdoor environment (garden, swimming pool, parking, public road, etc.)
Mechanism type	Double fixed base
Rated current	16A
Nominal voltage	250V~ (50/60 Hz)
Connection type	Screw connection
Tube inlet	Up to Ø 20 mm
Flexible cable section	Up to 2.5 mm <sup>2</sup>
Rigid cable section	Up to 2.5 mm <sup>2</sup>
Power	3680 W
Dimensions	127 x 80 x 55
Monobloc (with frame included)	Yes
Frame color	Grey

### Technical data

Insulation class	Class II
Heat resistance (Ball pressure)	70/125 °C
Installation temperature	-5 °C -> +60 °C
Free of halogens	Yes

## Regulations

CE marking	Yes
According to Regulations	NF C61-314
According to Regulations UNE/EN	UNE 20315-1-1:2017 UNE 20315-1-2:2017
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
NF certificate	Yes
In accordance with the Regulation (EU) 2023/988 of the European Parliament and of the Council on general product safety	Yes

## Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

## Logistics and packaging

Unit EAN code	8423220228245
EAN code container	8423220228238
EAN code packaging	18423220228235
Units packaging	10
Units carton	60
Pallet Units	1260
Packaging Measurements cm	28x19,5x14
Packaging Measures cm	45,5x41,5x30
Unit weight (g)	204,4
Container Weight (Kg)	2,156
Packaging Weight (Kg)	13,704
Tariff code	85366990

## Documentation and downloads



Commercial doc. (2.27MB)



Safety Information (0.38MB)



Watertight switch IP54/44 (Solera)



Assembly watertight switches IP54/44 (Solera)