
9151616

16 x 16 mm trunking. Screw fixing.

16 x 16 mm trunking. Screw fixing.IP40. 2 m length. PVC material (M1) insulator "flame retardant". Working temperature: code 321. Shock resistance: medium or strong impacts. Useful surface 182 mm². Bottom closure.
Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Installation method	Surface
Use	Domestic / Tertiary
Location type	Inside
Fixing method	Screw
Dimensions (Height x Width - mm)	16 x 16
Useful surface (mm²)	182
Compartment	One
Composition	Base + lid
Closing	Lower
Section length	2 m
Material	PVC (M1)

Technical data

Protection Degree (IP)	IP40
Fire resistance (GWEPT)	850 ºC
Work temperature	Code: 321
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 50085-1:2006
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
According to European Directive 2012/19/UE (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).

Logistics and packaging

Unit EAN code	8423220039308
EAN code container	8423220039308
EAN code packaging	18423220039305
Units packaging	0
Units carton	40
Pallet Units	2640
Packaging Measures cm	200x7,8x8,9
Packaging Weight (Kg)	4,46
Tariff code	39269097