

Base trunking 40 x 70 mm. Screw fixing.

Base trunking 40 x 70 mm. Screw fixing. 2 m length. PVC material (M1) insulator "flame retardant". Working temperature: code 321. Shock resistance: medium or strong impacts.



Features

Installation method	Surface
Use	Domestic / Tertiary
Location type	Inside
Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Fixing method	Screw
Dimensions (Height x Width - mm)	40 x 70
Compartment	One
Composition	Base lâche
Closing	Lower
Material	PVC (M1)

Technical data

Fire resistance (GWEPT)	850 °C
Work temperature	Code: 321

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 50085-1:2006

In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
--	-----

According to European Directive 2014/35 / EU. Low voltage directive	Yes
---	-----

Sustainability

According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
---	--

According to European Directive 2012/19/UE (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).
--	---

Logistics and packaging

Unit EAN code	8423220019454
---------------	---------------

EAN code container	8423220019454
--------------------	---------------

EAN code packaging	18423220019451
--------------------	----------------

Units packaging	1
-----------------	---

Units carton	48
--------------	----

Pallet Units	768
--------------	-----

Packaging Measures cm	200x23x20
-----------------------	-----------

Packaging Weight (Kg)	13,94992
-----------------------	----------

Tariff code	39259020
-------------	----------

Documentation and downloads



Safety Information (0.38MB)