

### 10 x 16 mm trunking. With self-adhesives and for screws fixin.

10 x 16 mm trunking. With self-adhesives and for screws fixin. IP40. 2 m length. PVC material (M1) insulator "flame retardant". Graphite color. Working temperature: code 321. Shock resistance: medium or strong impacts. Useful surface 104 mm<sup>2</sup>. Bottom closure.

Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)









#### **Features**

Installation method	Surface
Use	Domestic / Tertiary
Location type	Inside
Fixing method	Self-adhesive and screw base
Dimensions (Height x Width - mm)	10 x 16
Useful surface (mm²)	104
Compartment	One
Composition	Base + lid
Closing	Lower
Section length	2 m
Material	PVC (M1)

#### **Technical data**

Protection Degree (IP)	IP40
Fire resistance (GWEPT)	850 °C
Work temperature	Code: 321
Free of halogens	Yes

### Regulations

CE marking	Yes		



UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 50085-1:2006
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

# Sustainability

According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
According to European Directive 2012/19/UE (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).

# Logistics and packaging

Unit EAN code	8423220270954
EAN code container	8423220270954
Units carton	36
Pallet Units	8470