




Flush & surface mounting IT board available for Hollow as well as Solid walls

Thermoplastic material



- Complies with directive 2014/35/UE.
- Complies with directive 2011/65/UE (RoHS).
- In accordance with EN 62 208 and EN 60670-1.
- IP40 (door closed). IK07.
- Class II.
- GWT 650 °C / For hollow walls 850 °C.
- 70C° ball pressure test.

Solid & Hollow walls



Grid for heat dissipation.



Lock system (optional).



Claw fixing for flush distribution boards.

Accessories included


Protection against plaster




Instructions for use



1 DIN Rail



2 Multiperforated plate assembly



Ref. PL-MP28

Accessories not included in all references

4 Clamping support hollow walls



Ref. BOLSA-5430H

Reference	USE - DESCRIPTION	Accessories INCLUDED	Additional information	Pack / Carton	Net Price
5508-IT	Ref. Surface	---	Reversible	1/4	
5508L-IT	Ref. Surface with key	---	Reversible	1/4	
5504-IT	Ref. Flush Solid Walls	---	Reversible	1/4	
5504L-IT	Ref. Flush Solid Walls with key	---	Reversible	1/4	
5504HH-IT	Ref. Flush Hollow Walls	BOLSA-5430H	Reversible	1/4	
5504HHL-IT	Ref. Flush Hollow Walls with key	BOLSA-5430H	Reversible	1/4	

