

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

BOXES AND ENCLOSURES FOR ELECTRICAL ACCESSORIES

Name and address of the applicant

PORTALAMPARAS Y ACCESORIOS SOLERA, S.A.
PI FUENTE DEL JARRO, CL VILLA DE MADRID, 53
46988 PATERNA (Valencia - Spain)

Name and address of the manufacturer

PORTALAMPARAS Y ACCESORIOS SOLERA, S.A.
PI FUENTE DEL JARRO, CL VILLA DE MADRID, 53
46988 PATERNA (Valencia - Spain)

Name and address of the factory

SAME AS ABOVE

Note: When more than one factory, please report on page 2 Additional Information on page 2

Ratings and principal characteristics

See Annex

Trademark (if any)

SOLERA

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

Y686; Y715; Y716; Y815P; Y816P; Y886P

Additional information (if necessary may also be reported on page 2)

 Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60670-1:2015
IEC 60670-22:2003
IEC 60670-22:2003/AMD1:2015

As shown in the Test Report Ref. No. which forms part of this Certificate

CEL-0212/20-1_1

This CB Test Certificate is issued by the National Certification Body

AENOR INTERNACIONAL S.A.U.
Cl Génova, 6
ES-28004 MADRID (SPAIN)

Date: 2020-07-17


Signature: Rafael GARCÍA MEIRO
Chief Executive Officer

ANNEX TO CB CERTIFICATE N° ES2325-AENOR

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Trade Mark: SOLERA

Product: BOXES AND ENCLOSURES FOR ELECTRICAL ACCESSORIES

Type Ref.	Type of product	Installation method	Temperature during installation	Maximun temperature during casting process	Degree of protection (IP)	Dimension (mm) Breadth x High x Depth	Additional information
Y686	Caja/Box	Superficie/ surface- mounting	-5 a/to +60 °C	60 °C	IP55	220 x 170 x 80	Estanca; IK08
Y715	Caja/Box	Superficie/ surface- mounting	-5 a/to +60 °C	60 °C	IP55	100 x 100 x 55	Estanca; IK08
Y716	Caja/Box	Superficie/ surface- mounting	-5 a/to +60 °C	60 °C	IP55	153 x 110 x 65	Estanca; IK08
Y815P	Caja/Box	Superficie/ surface- mounting	-5 a/to +60 °C	60 °C	IP65	100x 100 x 55	Estanca; IK08
Y816P	Caja/Box	Superficie/ surface- mounting	-5 a/to +60 °C	60 °C	IP65	153 x 110 x 65	Estanca; IK08
Y886P	Caja/Box	Superficie/ surface- mounting	-5 a/to +60 °C	60 °C	IP65	220 x 170 x 80	Estanca; IK08